

PALMA

Design by Antoni Arola.

Reference

3736.

Application

Hanging lamps

Installation type

Surface

Description

Nature takes control of the space. With the pendant lamps the interior ambience takes on a life of its own with the possibility of integrating plants with the lighting compositions.

Diffuser

Blow-glass diffuser

Materials

Profile: Aluminum

Diffuser: Blown-glass

Flowerpot: PMMA (thermoplastic polymer)

Finish




3736-18 Graphite (ADAPTA RF 9913 WX)



3736-93 White (RAL 9016)

Sketch



Electrical characteristics

6 x LED 4,6W 500mA

AND

1 x LED 2W 500mA



Total 29.6 W



VIBIA



Light source: 2700K CRI >90 2057.53 lm

Driver included: CC - Constant Current 500 mA 110-240V 50/60Hz

Electronic dimming DALI 1-10V Push

[ficha.fichatecnicaproducto.regulacion.opcional SMART](#)

Technical characteristics

- Plants not included

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.2219 m³ /

Gross weight 12.3 kg. / Net weight 8.2 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 1912.81 lm

Maximum value : 65.09 cd/klm

Light position : C=0.00 G=1.00

Symmetry on the planes : Asymmetric

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates

