



# ROBY IP44 UPDATE

CEILING SURFACE



## 1.6

LED 13W | 220-240VAC | 50-60Hz  
AC PCB 3-step low flicker  
phase-cut dim | aluminium  
powder coated brushed | opal  
PMMA cover



2700K | >90 CRI | 750lm

	CODE
	135184W3
	135184B3

3000K | >90 CRI | 820lm


	CODE
	135184W5
	135184B5

### OPTIONAL

dimmer

	CODE
for switch	90019017
for din rail	90019018

more specs on page 591



## 2.6

LED 18W | 220-240VAC | 50-60Hz  
AC PCB 3-step low flicker  
phase-cut dim | aluminium  
powder coated brushed | opal  
PMMA cover



2700K | >90 CRI | 1130lm

	CODE
	135284W3
	135284B3

3000K | >90 CRI | 1250lm


	CODE
	135284W5
	135284B5

### OPTIONAL

dimmer

	CODE
for switch	90019017
for din rail	90019018

more specs on page 591



## 3.5

LED 32W | 220-240VAC | 50-60Hz  
AC PCB 3-step low flicker  
phase-cut dim | aluminium  
powder coated brushed | opal  
PMMA cover



2700K | >90 CRI | 1680lm

	CODE
	135384W3
	135384B3

3000K | >90 CRI | 1800lm

	CODE
	135384W5
	135384B5

### OPTIONAL

dimmer

	CODE
for switch	90019017
for din rail	90019018

more specs on page 591