


PRODUCT DATA SHEET

# Skydro Ceiling Led 3000K



IP20 🕘 🕷 🕅 Dimmerable: +O-

# TECHNICAL DRAWINGS



DESI	GN	BY

Ross Lovegrove

### DESCRIPTION

Ceiling lamp, a further development of the Hydro series. A series of pebbles forms a bright sky reflecting the light that bounces on its biomorphic surfaces.

FEATURES			
Article Code: Colour: Installation: Environment:	1245110A Polished chrome Ceiling Indoor	Material: Series: Emission:	Aluminium, steel, ABS Design, Scenarios Indirect
DIMENSIONS			
Height: Depth:	cm 136 cm 42	Glow Wire Test:	960°C
INCLUDED SOURCES			
Category: Number: Watt: Delivered lumens output (lm) Type:	LED 1 29W : 4230lm 0	Color temperature (K): Color Tolerance: CRI:	3000K MacAdam 2SDCM 90
LUMINAIRE			
Watt:	29W	Delivered lumens output (lm) CCT: Efficiency: Efficacy: CRI: Dimmable Typology:	: 1662lm 3000K 58% 57.31lm/W 90 Push
Notes			

#### Notes

Available in two versions: the first, in which the indirect light comes from a lighting unit integrated into the lamp, the second, in which the indirect light comes from a wall projector that is separate from the lamp. Skydro is a sectional unit that enables numerous elements to be added. To assemble the multiple units it needs - in addition to the basic units (with or without light source) - an assembly kit (template) and cable kits for the electrical connection.



# ACCESSORIES

NO IMAGE AVAILABLE	NO IMAGE AVAILABLE	NO IMAGE AVAILABLE
SKYDRO PLAFONE	SKYDRO PLAFONE	SKYDRO PLAFONE
KIT MONTAGGIO	LED KIT CAVI	*
MODULI	COLLEG.	1234010A
1235010A	1246010A	